

SLIM SMD LED FLOODLIGHTS





SKU Code: T201 | T220 | T202 | T203 | T204 | T205 | T221 | T206 | T207 | T208 | T209 | T210 | T211 | T212

Description

Our Slim and Sleek Design is the most advanced LED floodlight on the market, with an attractive ultra-thin design and innovative high voltage LED chips. Suitable for use both indoors and outdoors and available in black finish.

Features

- Daylight (6000K), Cool White (4000K) and Warm White (3000K) options
- · High grade aluminum body and toughened glass lens
- · Ra>70, P.F>0.9, THD<20
- Complete with mounting bracket and 50cm input cable length. Input cable dia 3x0.75mm2
- Instant start and restart can be used with PIR sensors
- · 30,000 hours rated life
- · 2 year warranty
- Approved by CÉ EMC

Technical Specification		
Voltage	220-245V~ 50/60Hz	
Lamp	SMD LED	
Colour temperature	6000K/4000K/3000K	
IP rating	IP65	

Range						
10W	6000K	BK	T201			
10W	4000K	BK	T220			
10W	3000K	BK	T202			
20W	6000K	BK	T203			
20W	3000K	BK	T204			
30W	6000K	BK	T205			
30W	4000K	BK	T221			
30W	6000K	BK	T206			
50W	6000K	BK	T207			
50W	4000K	BK	T208			
50W	3000K	BK	T209			
100W	6000K	BK	T210			
100W	4000K	BK	T211			
100W	100W 3000K		T212			

11111111

RESERVE

: mmm :

18181111

Dimensio	ons (mm), Beam Angle & Lumens			
	Lumen Output	Housing Weight	Fitting Dimensions (L x H x D)	
10W	800lm	50g	100x80x19mm	
20W	1600lm	100g	128x97x26mm	
30W	2400lm	180g	157x117x33mm	
50W	4000lm	330g	203x150x33mm	
100W	8000lm	480g	313x207x33mm	

Brand of LED Chip: SANAN, Housing Material: Aluminum, Bracket Material: Iron



30W

50W

10W

20W

100W