

24W LED BULKHEAD CEILING LIGHT WITH MICROWAVE SENSOR







SKU Code: T754 - White



424W

IP65

This fitting is a 24W LED bulkhead light fitting ideal for outdoor wall lighting complete with a microwave motion sensor. It has an IP65 rating (it is waterproof) and offers a 4000K light. With a 110mm projection and approx. 280mm diameter, this bulkhead has a polycarbonate base in white, a gloss white trim ring, and an opal diffuser.

This range of LED bulkheads are robust and versatile with an IP65 rating which protects from dust and jets of water. The sensor is an active motion detector: it emits a high frequency electromagnetic wave 5.9Hz and receives its echo. The sensor detects the change in echo from movement in its detection zone. A microprocessor then triggers the switch light ON command.

Features

- Detection is possible through doors, panels of glass, and thin walls.
- They are ideal for hospitals, nursing homes, schools, and any other commercial or domestic environments, both indoors and outdoors as needed.
- Mains voltage: 240V supply 50/60Hz.
- 24W SMD LED lamp, 4000K.
- · Lumens: 2040lm
- · HF System: 5.8GHz CW radar
- Transmission power: <0.2mW

Wattage 24W Housing Material ABS Housing Colour White CCT 4000K Input Voltage 170V-250V, 50/60 Hz Product Measurement Ø280*63mm RA 80 PF >0.5 Dimmable No Power Supply Internal CE standard IC Driver Lumens Per Watt 85 Luminous flux 2040 lm Beam 180 IP Rating IP65 IK Rating IK10 Suitable temperature -20*+45 Switching cycles ≥15000 Starting time (Seconds) <15 Energy efficiency class A+ Microwave Sensor Inbuilt Microwave Sensor Static Power Dissipation <0.5W Microwave Frequencies 5.8 GHz +/- 75 MHz Microwave Power <0.2 mW Detection Range (Dimater x Height): 10m x 6m Detection Angle 30 ~ 150 Installation Height 6m Accessories Surface Mounting Kit Included Quick Connector Included Colour Box Dimension 290*75*390mm Product Weight with Colourbox 0.955 Kgs Pcs per Master Carton 5 pcs Master Carton Dimension 39.5X30.5X31CM Master Carton Weight 5.8 GHz +/- 75 MHz **TOTAL COLOUR SURVEY STAND SURVEY STAND SURVEY STAND SURVEY SURV	Specifications	
Housing Colour CCT 4000K Input Voltage Product Measurement RA 80 PF >0.5 Dimmable No Power Supply Internal CE standard IC Driver Lumens Per Watt Beam IP Rating IP Rating IK Rating Suitable temperature Switching cycles Starting time (Seconds) Energy efficiency class Microwave Sensor Static Power Dissipation Microwave Frequencies Microwave Power Detection Range Detection Angle Installation Height Accessories Quick Connector Included Colour Box Dimension Product Weight with Colourbox Master Carton Weight Master Carton Weight Mesou. 500 Mase And And Supplementation Microwave Sensor Surface Mounting Kit Included 0.995 Kgs Pcs per Master Carton Master Carton Weight 6.5Kgs	Wattage	24W
Input Voltage 170V-250V, 50/60 Hz Product Measurement Ø280*63mm RA 80 PF >0.5 Dimmable No Power Supply Internal CE standard IC Driver Lumens Per Watt 85 Luminous flux 2040 lm Beam 180 IP Rating IR10 Suitable temperature -20*+45 Switching cycles ≥15000 Starting time (Seconds) <15 Energy efficiency class A+ Microwave Sensor Inbuilt Microwave Sensor Static Power Dissipation <0.5W Microwave Frequencies 5.8 GHz +/-75 MHz Microwave Power <0.2 mW Detection Range (Dimater x Height): 10m x 6m Detection Angle 30 ~ 150 Installation Height 6m Accessories Surface Mounting Kit Included Quick Connector Included Colour Box Dimension 290*75*390mm Product Weight with Colourbox 0.955 Kgs Pcs per Master Carton 5 pcs Master Carton Weight 6.5Kgs	Housing Material	ABS
Input Voltage 170V-250V, 50/60 Hz Product Measurement Ø280*63mm RA 80 PF >0.5 Dimmable No Power Supply Internal CE standard IC Driver Lumens Per Watt 85 Luminous flux 2040 lm Beam 180 IP Rating IP65 IK Rating IK10 Suitable temperature -20*445 Switching cycles ≥15000 Starting time (Seconds) <15 Energy efficiency class A+ Microwave Sensor Inbuilt Microwave Sensor Static Power Dissipation <0.5W Microwave Frequencies 5.8 GHz +/-75 MHz Microwave Power <0.2 mW Detection Range (Dimater x Height): 10m x 6m Detection Angle 30 ~ 150 Installation Height 6m Accessories Surface Mounting Kit Included Quick Connector Included Colour Box Dimension 290*75*390mm Product Weight with Colourbox 0.955 Kgs Pcs per Master Carton 5 pcs Master Carton Dimension 39.5X30.5X31CM Master Carton Weight 6.5Kgs	Housing Colour	White
Product Measurement Ø280*63mm RA 80 PF >0.5 Dimmable No Power Supply Internal CE standard IC Driver Lumens Per Watt 85 Luminous flux 2040 lm Beam 180 IP Rating IR10 Suitable temperature -20~+45 Switching cycles ≥15000 Starting time (Seconds) <15 Energy efficiency class A+ Microwave Sensor Inbuilt Microwave Sensor Static Power Dissipation <0.5W Microwave Frequencies 5.8 GHz +/- 75 MHz Microwave Power <0.2 mW Detection Range (Dimater x Height): 10m x 6m Detection Angle 30 ~ 150 Installation Height 6m Accessories Surface Mounting Kit Included Quick Connector Included Colour Box Dimension 290*75*390mm Product Weight with Colourbox 0.955 Kgs Pcs per Master Carton 5 pcs Master Carton Dimension 39.5X30.5X31CM Master Carton Weight 6.5Kgs	CCT	4000K
RA PF >0.5 Dimmable No Power Supply Internal CE standard IC Driver Lumens Per Watt Beam 180 IP Rating IF65 IK Rating IK10 Suitable temperature Switching cycles Starting time (Seconds) Energy efficiency class A+ Microwave Sensor Inbuilt Microwave Sensor Static Power Dissipation Microwave Frequencies Detection Range Detection Angle Detection Angle Quick Connector Colour Box Dimension Product Weight with Colourbox Master Carton Dimension More Sungard Sunday Sunday Possible Standard IC Driver Internal CE standard Internal Internal CE standard IC Driver Internal CE standard Internal Int	Input Voltage	170V-250V, 50/60 Hz
PF Dimmable No Power Supply Internal CE standard IC Driver Lumens Per Watt Beam 180 IP Rating IK Rating IK Rating Suitable temperature Switching cycles Starting time (Seconds) Energy efficiency class A+ Microwave Sensor Inbuilt Microwave Sensor Static Power Dissipation Microwave Frequencies Detection Range Detection Angle Detection Angle INSUITABLE Microwave Suitable temperature -20~+45 Switching cycles ≥15000 Starting time (Seconds) -15 Energy efficiency class A+ Microwave Sensor Inbuilt Microwave Sensor Static Power Dissipation -0.5W Microwave Frequencies -0.2 mW Detection Range Detection Angle -0.2 mW Detection Angle -0.30 ~ 150 Installation Height -0.10 Installation Height -0.10 Accessories -0.10 Surface Mounting Kit Included -0.10 Included -0.10 Colour Box Dimension -0.955 Kgs -0.955 Kg	Product Measurement	Ø280*63mm
Dimmable Power Supply Internal CE standard IC Driver Lumens Per Watt Beam 180 IP Rating IF Rating IK Rating IK Rating Suitable temperature -20*+45 Switching cycles *15000 Starting time (Seconds) Energy efficiency class A+ Microwave Sensor Static Power Dissipation Microwave Frequencies Microwave Power Detection Range Detection Angle Installation Height Accessories Surface Mounting Kit Included Quick Connector Colour Box Dimension Product Weight with Colourbox Pcs per Master Carton Dimension Master Carton Weight Microweve Supplied Accessories No Internal CE standard IC Driver Internal CE standard Internal	RA	80
Power Supply Lumens Per Watt Beam IBO IP Rating IK Rating Suitable temperature Switching cycles Starting time (Seconds) Energy efficiency class Microwave Sensor Static Power Dissipation Microwave Prequencies Detection Range Detection Angle Detection Angle Accessories Quick Connector Colour Box Dimension Master Carton Dimension Master Carton Weight Devaring 180 IR10 180 IP65 IK10 S0445 IK10 S05445 IK10 S065 IK10 S180 IK10 S180 IK10 S180 S150 S180 S150 S150 S180 S1	PF	>0.5
Lumens Per Watt 85 Luminous flux 2040 lm Beam 180 IP Rating IP65 IK Rating IK10 Suitable temperature -20~+45 Switching cycles ≥15000 Starting time (Seconds) <15	Dimmable	No
Luminous flux 2040 lm Beam 180 IP Rating IP65 IK Rating IK10 Suitable temperature -20~+45 Switching cycles ≥15000 Starting time (Seconds) <15 Energy efficiency class A+ Microwave Sensor Inbuilt Microwave Sensor Static Power Dissipation <0.5W Microwave Frequencies 5.8 GHz +/- 75 MHz Microwave Power <0.2 mW Detection Range (Dimater x Height): 10m x 6m Detection Angle 30 ~ 150 Installation Height 6m Accessories Surface Mounting Kit Included Quick Connector Included Colour Box Dimension 290*75*390mm Product Weight with Colourbox 0.955 Kgs Pcs per Master Carton 5 pcs Master Carton Dimension 39.5X30.5X31CM Master Carton Weight 6.5Kgs	Power Supply	Internal CE standard IC Driver
Beam 180 IP Rating IP65 IK Rating IK10 Suitable temperature -20~+45 Switching cycles ≥15000 Starting time (Seconds) <15 Energy efficiency class A+ Microwave Sensor Inbuilt Microwave Sensor Static Power Dissipation <0.5W Microwave Frequencies 5.8 GHz +/- 75 MHz Microwave Power <0.2 mW Detection Range (Dimater x Height): 10m x 6m Detection Angle 30 ~ 150 Installation Height 6m Accessories Surface Mounting Kit Included Quick Connector Included Colour Box Dimension 290*75*390mm Product Weight with Colourbox 0.955 Kgs Pcs per Master Carton 5 pcs Master Carton Dimension 39.5X30.5X31CM Master Carton Weight 6.5Kgs	Lumens Per Watt	85
IP Rating IK Rating IK Rating IK Rating IK ID Suitable temperature -20~+45 Switching cycles \$15000 Starting time (Seconds) Energy efficiency class A+ Microwave Sensor Inbuilt Microwave Sensor Static Power Dissipation Microwave Frequencies 5.8 GHz +/- 75 MHz Microwave Power O.2 mW Detection Range (Dimater x Height): 10m x 6m Detection Angle 30 ~ 150 Installation Height Accessories Surface Mounting Kit Included Quick Connector Included Colour Box Dimension Product Weight with Colourbox Pcs per Master Carton Master Carton Dimension 39.5X30.5X31CM Master Carton Weight 6.5Kgs	Luminous flux	2040 lm
IK Rating Suitable temperature Switching cycles Starting time (Seconds) Energy efficiency class Microwave Sensor Static Power Dissipation Microwave Frequencies Microwave Power Detection Range Detection Angle Installation Height Accessories Quick Connector Colour Box Dimension Product Weight with Colourbox Master Carton Weight Mix10 A15 A+ Microwave Sensor Inbuilt Microwave Sensor S.8 GHz +/- 75 MHz (D.5W Microwave Power ⟨0.2 mW (Dimater x Height): 10m x 6m 30 ~ 150 Installation Height 6m Accessories Surface Mounting Kit Included Quick Connector Included Colour Box Dimension 290*75*390mm Product Weight with Colourbox D.955 Kgs Pcs per Master Carton 39.5X30.5X31CM Master Carton Weight 6.5Kgs	Beam	180
Suitable temperature -20~+45 Switching cycles ≥15000 Starting time (Seconds) <15 Energy efficiency class A+ Microwave Sensor Inbuilt Microwave Sensor Static Power Dissipation <0.5W Microwave Frequencies 5.8 GHz +/- 75 MHz Microwave Power <0.2 mW Detection Range (Dimater x Height): 10m x 6m Detection Angle 30 ~ 150 Installation Height 6m Accessories Surface Mounting Kit Included Quick Connector Included Colour Box Dimension 290*75*390mm Product Weight with Colourbox 0.955 Kgs Pcs per Master Carton 5 pcs Master Carton Dimension 39.5X30.5X31CM Master Carton Weight 6.5Kgs	IP Rating	IP65
Switching cycles ≥15000 Starting time (Seconds) <15 Energy efficiency class A+ Microwave Sensor Inbuilt Microwave Sensor Static Power Dissipation <0.5W Microwave Frequencies 5.8 GHz +/- 75 MHz Microwave Power <0.2 mW Detection Range (Dimater x Height): 10m x 6m Detection Angle 30 ~ 150 Installation Height 6m Accessories Surface Mounting Kit Included Quick Connector Included Colour Box Dimension 290*75*390mm Product Weight with Colourbox 0.955 Kgs Pcs per Master Carton 5 pcs Master Carton Dimension 39.5X30.5X31CM Master Carton Weight 6.5Kgs	IK Rating	IK10
Starting time (Seconds) Energy efficiency class A+ Microwave Sensor Inbuilt Microwave Sensor Static Power Dissipation Accessories Detection Angle Installation Height Accessories Quick Connector Colour Box Dimension Product Weight with Colourbox Master Carton Weight A+ A+ A+ A+ A+ Anicrowave Sensor Inbuilt Microwave Sensor S.8 GHz +/- 75 MHz A.2.2 mW (Dimater x Height): 10m x 6m Box 150 Surface Mounting Kit Included Included Colour Box Dimension Detection Angle Surface Mounting Kit Included Colour Box Dimension Detector Detection Angle Surface Mounting Kit Included Colour Box Dimension Detection Angle Surface Mounting Kit Included Colour Box Dimension Detection Angle Surface Mounting Kit Included Colour Box Dimension Detection Angle Surface Mounting Kit Included Colour Box Dimension Detection Angle Surface Mounting Kit Included Colour Box Dimension Detection Angle Surface Mounting Kit Included Detection Angle Surface Mounting Kit Included Detection Angle Surface Mounting Kit Included Colour Box Dimension Detection Angle Surface Mounting Kit Included Colour Box Dimension Detection Angle Surface Mounting Kit Included Detection Angle Detection Angle	Suitable temperature	-20~+45
Energy efficiency class Microwave Sensor Static Power Dissipation Microwave Frequencies S.8 GHz +/- 75 MHz Microwave Power O.2 mW Detection Range (Dimater x Height): 10m x 6m Detection Angle Installation Height Accessories Surface Mounting Kit Included Quick Connector Included Colour Box Dimension Product Weight with Colourbox Pcs per Master Carton Master Carton Dimension Master Carton Weight A+ A+ A+ A+ Aircrowave Sensor (D.5W Surface Mounting Kit Included Detection Angle Detection Angle Surface Mounting Kit Included Detection Angle Detection Angle Surface Mounting Kit Included Detection Angle Detection Angle Detection Angle Surface Mounting Kit Included Detection Angle Detection Angle Detection Angle Detection Angle Surface Mounting Kit Included Detection Angle Detect	Switching cycles	≥15000
Microwave Sensor Static Power Dissipation Microwave Frequencies S.8 GHz +/- 75 MHz Microwave Power O.2 mW Detection Range (Dimater x Height): 10m x 6m Detection Angle Installation Height Gm Accessories Surface Mounting Kit Included Quick Connector Included Colour Box Dimension Product Weight with Colourbox Pcs per Master Carton Master Carton Dimension 10.5 W 10	Starting time (Seconds)	<15
Static Power Dissipation <0.5W Microwave Frequencies 5.8 GHz +/- 75 MHz Microwave Power <0.2 mW Detection Range (Dimater x Height): 10m x 6m Detection Angle 30 ~ 150 Installation Height 6m Accessories Surface Mounting Kit Included Quick Connector Included Colour Box Dimension 290*75*390mm Product Weight with Colourbox 0.955 Kgs Pcs per Master Carton 5 pcs Master Carton Dimension 39.5X30.5X31CM Master Carton Weight 6.5Kgs	Energy efficiency class	A+
Microwave Frequencies 5.8 GHz +/- 75 MHz Microwave Power <0.2 mW Detection Range (Dimater x Height): 10m x 6m Detection Angle 30 ~ 150 Installation Height 6m Accessories Surface Mounting Kit Included Quick Connector Included Colour Box Dimension 290*75*390mm Product Weight with Colourbox 0.955 Kgs Pcs per Master Carton 5 pcs Master Carton Dimension 39.5X30.5X31CM Master Carton Weight 6.5Kgs	Microwave Sensor	Inbuilt Microwave Sensor
Microwave Power <0.2 mW Detection Range (Dimater x Height): 10m x 6m Detection Angle 30 ~ 150 Installation Height 6m Accessories Surface Mounting Kit Included Quick Connector Included Colour Box Dimension 290*75*390mm Product Weight with Colourbox 0.955 Kgs Pcs per Master Carton 5 pcs Master Carton Dimension 39.5X30.5X31CM Master Carton Weight 6.5Kgs	Static Power Dissipation	<0.5W
Detection Range (Dimater x Height): 10m x 6m Detection Angle 30 ~ 150 Installation Height 6m Accessories Surface Mounting Kit Included Quick Connector Included Colour Box Dimension 290*75*390mm Product Weight with Colourbox 0.955 Kgs Pcs per Master Carton 5 pcs Master Carton Dimension 39.5X30.5X31CM Master Carton Weight 6.5Kgs	Microwave Frequencies	5.8 GHz +/- 75 MHz
Detection Angle 30 ~ 150 Installation Height 6m Accessories Surface Mounting Kit Included Quick Connector Included Colour Box Dimension 290*75*390mm Product Weight with Colourbox 0.955 Kgs Pcs per Master Carton 5 pcs Master Carton Dimension 39.5X30.5X31CM Master Carton Weight 6.5Kgs	Microwave Power	<0.2 mW
Installation Height Accessories Surface Mounting Kit Included Quick Connector Included Colour Box Dimension Product Weight with Colourbox Pcs per Master Carton Master Carton Dimension June 10 5 pcs Master Carton Dimension 39.5X30.5X31CM Master Carton Weight 6.5Kgs	Detection Range	(Dimater x Height): 10m x 6m
Accessories Surface Mounting Kit Included Quick Connector Included Colour Box Dimension 290*75*390mm Product Weight with Colourbox 0.955 Kgs Pcs per Master Carton 5 pcs Master Carton Dimension 39.5X30.5X31CM Master Carton Weight 6.5Kgs	Detection Angle	30 ~ 150
Quick Connector Included Colour Box Dimension 290*75*390mm Product Weight with Colourbox 0.955 Kgs Pcs per Master Carton 5 pcs Master Carton Dimension 39.5X30.5X31CM Master Carton Weight 6.5Kgs	Installation Height	6m
Colour Box Dimension 290*75*390mm Product Weight with Colourbox 0.955 Kgs Pcs per Master Carton 5 pcs Master Carton Dimension 39.5X30.5X31CM Master Carton Weight 6.5Kgs	Accessories	Surface Mounting Kit Included
Product Weight with Colourbox	Quick Connector	Included
Pcs per Master Carton 5 pcs Master Carton Dimension 39.5X30.5X31CM Master Carton Weight 6.5Kgs	Colour Box Dimension	290*75*390mm
Master Carton Dimension 39.5X30.5X31CM Master Carton Weight 6.5Kgs	Product Weight with Colourbox	0.955 Kgs
Master Carton Weight 6.5Kgs	Pcs per Master Carton	5 pcs
	Master Carton Dimension	39.5X30.5X31CM
Lifetime 20000 hours	Master Carton Weight	6.5Kgs
בוופנוווופ 30000 110005	Lifetime	30000 hours